

## Technical Data Sheet

### General

Article number: 6660  
Description: Colad Translucent Spraymask (Extra Wide)  
(6 m x 100 m)



### Specifications

Form: Film on roll.  
Material: HD-PE.  
Color: Translucent.  
Film width x length: 6 meter x 100 meter.  
Roll width: 1 meter.  
Temperature resistance: 120 °C.  
Solubility in water: Insoluble.  
Properties: Static - the film 'clings' to the surface.  
Specially treated for optimal paint adhesion.  
Can be used with infrared drying (max. 120°C).  
Extra wide.  
Packaging: Per roll in a carton box, 25 carton boxes per pallet.  
Carton box can be used as a dispenser.

### Application

Colad products are worked up and designed for use in car body shops. The Masking Films are ideal for quick and efficient covering of a vehicle and protect it against overspray, dirt and dust. Colad Translucent Spraymask (extra wide) with paint adhesion - primer and/or paint adheres permanently to the film. This film has static properties, is easy to cut with art.no. 2070 or 2075 and can be used with infrared drying (max. 120°C). Because of the wide dimensions this film is very suitable for masking large vehicles (like Vans, SUV's and Trucks) sideways. By using the Colad Mobile Foil Dispenser (Art.no. 2060) covering can be done by one person. Colad Translucent Spraymask (Extra Wide) is environmentally friendly and can be recycled, safely incinerated or buried in the ground.

#### Used for:

- Sanding / Surface Preparation
- Painting

+ Sideways masking



Paint adhesion



High static power



High tensile strength



Infrared drying max. 120°C



Extra wide 6m

The Colad assortment has a complete range of Masking Film for quick and efficient masking, together with the 6340 (3,8 m x 200 m) 6340300 (3,8 m x 300 m), 6345 (4 m x 150 m, 17 micron), 6365 (4 m x 300 m), 6375 (4 m x 150 m) and the 6660-5 (5 m x 120 m) there is a fitted film for every job.

### Created by :

E.M.M. International BV  
Marsweg 59  
8013 PE Zwolle  
The Netherlands

phone +31 38 4676600

fax +31 38 4676699

[www.emm.com](http://www.emm.com)