



# C67 UNIHARDENER UHS SLOW

## A) DESCRIPTION AND FIELDS OF APPLICATION:

Rapid ultra high solid hardener for universal use. Provides higher thickness with fewer coats. It does not yellow, and is compatible with any acrylic or polyurethane, clear or coloured, 2k top coat. Recommended for temperatures greater than 18°C and for big surface.

## B) TECHNICAL DATA:

Composition	Polyisocyanic resins and solvents
Specific weight	1,018 ± 0,030 kg/l
Available colours	Neutral
Safety data	Refer to the safety sheet

## C) PROCESSING :

Mixing ratio by volume with H69 and H79 clear: is 2:1

## D) CAUTIONS:

- \* Hardeners for 2k products contain isocyanates and react with moisture.
- \* Tins must be kept properly closed; all processing equipment and containers used for mixing must be perfectly dry.

Technical indications and advices are based on our own experiences. We assure the perfect quality of products. However, being the utilization out of our control, we assume no responsibility on the results obtained

### INDUSTRIA CHIMICA REGGIANA - I.C.R. S.p.A.

42124 Reggio Emilia - Via M. Gasparini, 7 - Tel. +39 0522 517803 - Fax +39 0522 514384 - e-mail: icr@icrsprint.it - www.icrsprint.it

Uff. Comm.le Italia: 42124 Reggio Emilia - Via Neviani, 5 - Tel. +39 0522 517803 - Fax +39 0522 231819

International Department: 42124 Reggio Emilia - Via Neviani, 5 - Tel. +39 0522 513738 - Fax +39 0522 512446

Stabilimento: 42124 Reggio Emilia - Via M. Gasparini, 7 - Tel. +39 0522 517803 - Fax +39 0522 514384

Stabilimento: 26817 S. Martino in Strada (LO) - Via del Commercio, 1 - Tel. +39 0371 475313 - Fax +39 0371 475370

CAPITALE SOC. € 557.820,00 - R.E.A. N. 82109 M. R.E. 000534 - Reg. Imprese, COD. FISC. e PART. IVA 00140910357