



C70 HARDENER EPOS PRIMER

Hardener for epoxy primers

A) DESCRIPTION AND FIELDS OF APPLICATION:

Hardener formulated with special adduct. Ideal for wet on wet application to have excellent chemical resistance and anticorrosion properties and superior adhesion..

B) TECHNICAL DATA:

Composition	Adduct
Specific weight	0,95 ± 0,03kg/l
Available colours	Light yellow
Safety data	Refer to the safety sheet

C) PROCESSING :

Use in a ratio of 2:1 by volume or 30% by weight; i.e 100 g of F70 2k Epoxy Primer with 30 g of C70 hardener.

D) CAUTIONS:

- * Dosing errors consisting of 10% more or less of the percentage of hardener will jeopardize the end results of the product.
- * Tins must be kept properly closed; all processing equipment and containers used for mixing must be perfectly dry.

Technical indications and advices are based on our own experiences. We assure the perfect quality of products. However, being the utilization out of our control, we assume no responsibility on the results obtained

INDUSTRIA CHIMICA REGGIANA - I.C.R. S.p.A.

42124 Reggio Emilia - Via M. Gasparini, 7 - Tel. +39 0522 517803 - Fax +39 0522 514384 - e-mail: icr@icrsprint.it - www.icrsprint.it

Uff. Comm.le Italia: 42124 Reggio Emilia - Via Neviani, 5 - Tel. +39 0522 517803 - Fax +39 0522 231819

International Department: 42124 Reggio Emilia - Via Neviani, 5 - Tel. +39 0522 513738 - Fax +39 0522 512446

Stabilimento: 42124 Reggio Emilia - Via M. Gasparini, 7 - Tel. +39 0522 517803 - Fax +39 0522 514384

Stabilimento: 26817 S. Martino in Strada (LO) - Via del Commercio, 1 - Tel. +39 0371 475313 - Fax +39 0371 475370

CAPITALE SOC. € 557.820,00 - R.E.A. N. 82109 M. R.E. 000534 - Reg. Imprese, COD. FISC. e PART. IVA 00140910357