



D12 DILUENTE POLIESTERE

Thinner for F17, F18 polyester spray fillers

A) DESCRIPTION AND FIELDS OF APPLICATION:

Especially formulated to obtain a great reduction in viscosity. Promotes better flow and prevents blushing. It insures fast drying and easy sanding.

B) TECHNICAL DATA:

Composition	Ester base solvents
Specific weight	0,9 ± 0,1
Available colours	Colourless
Safety data	See safety data sheet

C) PROCESSING :

For all spraying type polyester fillers.

Mixing ratio : Add 2% to 10% depending on the required viscosity

D) CAUTIONS:

* Do not utilize the product at temperatures below 5°C.

Technical indications and advices are based on our own experiences. We assure the perfect quality of products. However, being the utilization out of our control, we assume no responsibility on the results obtained

INDUSTRIA CHIMICA REGGIANA - I.C.R. S.p.A

42100 Reggio Emilia - Via M. Gasparini, 7 - Tel. +39 0522 517803 - Fax +39 0522 514384 - e-mail: icr@icrsprint.it - www.icrsprint.it

Uff. Comm.le Italia: 42100 **Reggio Emilia** - Via Neviani, 5 - Tel. +39 0522 517803 - Fax +39 0522 231819

International Department: 42100 **Reggio Emilia** - Via Neviani, 5 - Tel. +39 0522 513738 - Fax +39 0522 512446

Stabilimento: 42025 **Cavriago** - Via Nizzola, 5 - Tel. +39 0522 371818 - Fax +39 0522 575110

Stabilimento: 06074 **Perugia** - Via Trasimeno Ovest, 159/Z/13 - Tel. +39 075 518611 - Fax +39 075 5186125

CAPITALE SOC. € 557.820,00 – R.E.A. N. 82109 M. R.E. 000534 - Reg. Imprese, COD. FISC. e PART. IVA 00140910357