



For professional use only

Issue: March 2016
Superseded: July 2010

Kapci Thinners

Product description

Kapci Thinners are especially designed to suite the application viscosity and the drying time of Kapci Car Refinish products when used with Kapci Hardeners. Kapci Thinners optimize all painting conditions and assist in delivering highly reliable application processes.

Products

Product	Description	
Kapci 600F	Fast Thinner	Universal thinner for 1K Etch Primers, TPA products, Clearcoats, 2K Acrylic Fillers, 2K Sealers, 2K Acrylic Topcoats, Basecoats and Clearcoats. It adjusts the application viscosity at low temperatures from 15°C to 20°C.
Kapci 600	Normal Thinner	Universal thinner for 1K Etch Primers, TPA products, 2K Acrylic Fillers, 2K Sealers, 2K Acrylic Paints, Basecoats and Clearcoats. It adjusts the application viscosity at normal temperatures from 20°C-25°C.
Kapci 601	Slow Thinner	Universal thinner for TPA products, 2K Acrylic Fillers, 2K Sealers, 2K Acrylic Paints, Basecoats and Clearcoats. It adjusts the application viscosity at temperature above 30°C.
Kapci 602	Extra Slow Thinner	Universal thinner for 2K Acrylic Fillers, 2K Sealers, 2K Acrylic Paints and Clearcoats. It is not recommended for Basecoats. It adjusts the application viscosity at temperature above 35°C.
Kapci 610	Metallic Thinner	Thinner used only in Basecoats.

Choice of thinners

The recommendations in the table below, are for guidance only. Please refer to TDSs of the respective 2K products for more detailed information about the selection of the Thinners.

These products are for the professional painting of automotive vehicles only after reference to the manufacturer's Material Safety Data Sheets (MSDS)



KAPCI
COATINGS

For professional use only

Issue: March 2016
Superseded: July 2010

Thinner	600F	600	601	602	610
Complete car or large objects	Unsuitable	Suitable	Suitable	Suitable	Suitable
Partial repair	Suitable	Suitable	Suitable	Suitable	Suitable
15°C - 20°C	Suitable	Suitable	Unsuitable	Unsuitable	Suitable
20°C- 25°C	Not particularly suitable	Suitable	Not particularly suitable	Not particularly suitable	Suitable
Above 30°C	Unsuitable	Suitable	Suitable	Suitable	Suitable
Above 35°C	Unsuitable	Not particularly suitable	Suitable	Suitable	Suitable

General notes

1. Kapci 602 Extra Slow Thinner should not be used with Kapci Basecoats.
2. Kapci 610 is used only for Kapci Basecoats and should not be mixed with other Kapci 2K products.

Health and Safety

1. For full Health and Safety information please refer to Material Safety Data Sheet (MSDS).
2. Observe the precautionary notices displayed on the container.
3. Goggles and suitable protective equipment must be worn while using these products.
4. Good ventilation must be provided in the working environment.

IMPORTANT NOTE: These products are for professional use only. The information in this Technical Data Sheet is based on our best knowledge and given for information purposes only without any obligation as we do not have control over the quality and conditions of the surface, or over many factors affecting the use and application of the product. Always read the Material Safety Data Sheet and the Technical Data Sheet for this product if available.

Rev (01) 03/2016