



V01 ADDITIVO ANTISCHIVANTE

Anticratering additive

A) DESCRIPTION AND FIELDS OF APPLICATION:

Anticratering additive used to reduce craters and popping on surface caused by environmental pollutants. Dosage 0,1-0,5 % for 1k-2k coating.

V01, if used in not correct dosage can increase sagging and losing intercoat adhesion

B) TECHNICAL DATA:

Composition	Mixture of solvents and additive
Specific weight	0,90 ± 0,02
Available colours	Colourless
Safety data	See safety data sheet

C) PROCESSING :

To use 0,1-0,5 % of additive on 1k or 2k coating and mix very well before to spray.

D) CAUTIONS:

* Exaggerate dosage can cause sagging and losing intercoat adhesion.

Technical indications and advices are based on our own experiences. We assure the perfect quality of products. However, being the utilization out of our control, we assume no responsibility on the results obtained

INDUSTRIA CHIMICA REGGIANA - I.C.R. S.p.A

42124 Reggio Emilia - Via M. Gasparini, 7 - Tel. +39 0522 517803 - Fax +39 0522 514384 - e-mail: icr@icrsprint.it - www.icrsprint.it

Off. Comm.le Italia: 42124 Reggio Emilia - Via Neviani, 5 - Tel. +39 0522 517803 - Fax +39 0522 231819

International Department: 42124 Reggio Emilia - Via Neviani, 5 - Tel. +39 0522 513738 - Fax +39 0522 512446

Stabilimento: 42124 Reggio Emilia - Via M. Gasparini, 7 - Tel. +39 0522 517803 - Fax +39 0522 514384

Stabilimento: 26817 S. Martino in Strada (LO) - Via del Commercio, 1 - Tel. +39 0371 475313 - Fax +39 0371 475370

CAPITALE SOC. € 557.820,00 - R.E.A. N. 82109 M. R.E. 000534 - Reg. Imprese, COD. FISC. e PART. IVA 00140910357